



ZIP 4-7 ZIP Retractable Ladder

ZIP 4-7 Overview

The retractable Zip ladder provides the simple solution to ceiling and loft access. Incorporating deep and wide anti-slip treads, a counterbalance spring ensures that the stairway can be operated with a minimum of effort. Telescopic hand rail is included as standard

Mounted on a headboard for easy installation.

STANDARD FEATURES

- 350mm x 140mm anti-slip treads as standard
- Telescopic Handrail
- Two heavy duty Counter balanced springs
- 18mm thick block wood backboard
- Manufactured from diecast aluminium

Materials:

Die cast aluminium alloy and Aluminium non-slip treads.

Operation:

Counter balanced springs are incorporated into the pivot bracket for easy opening.

Head Board:

The timber headboard is 18mm thick 'block wood'. This should not be attached to the hatch

Treads:

Standard tread width is 350mm by 140mm depth. Alternate sizes between 200mm - 380mm (140mm depth) also available.

Loading:

200Kg per tread. 500kg/m² overall structure.

Options:

Additional Grab rail
Additional steps

STANDARD SIZES					
Model	Headboard	Min. Aperture	Dimension 'X'	No. of Treads	WT. (Kg)
ZIP 4	Up to 2500	600 x 900	1210 x 1310	9	28
ZIP 5	2501 - 2790	600 x 900	1310 x 1410	10	30
ZIP 6	2791 - 3090	600 x 900	1410 x 1510	11	32
ZIP 7	3091 - 3390	600 x 950	1510 x 1610	12	34

Note: Add 50mm to minimum aperture Width to allow frame thickness of Jaktдор ceiling door. It is up to the customer to ensure the aperture size is large enough for their requirements.

