



ZIP 8

ZIP Retractable Ladder

ZIP 8 Overview

Surespan ZIP 8 heavy duty retractable ladders are made to order to suit your floor to ceiling height. This unit comes complete, ready mounted to a wooden ceiling door within a 19mm thick wooden casing 240mm deep. Certified to EN 14975.

The aperture size will be determined by the height of the ladder see below.

STANDARD FEATURES

- 350mm x 140mm anti-slip treads as standard
- Counterbalance spring action
- 19mm thick wooden casing 240mm deep
- Insulated Trap Door finished in white

Materials:

Die cast aluminium alloy with insulated wooden trapdoor. Aluminium non-slip treads.

Operation:

Counter balanced springs are incorporated into the pivot bracket for easy opening. Spring latch locked with operating pole.

Lining:

The timber surround is 19mm thick and 240mm high.

Trap Door:

62mm insulated sandwich trapdoor underside finished in white.

Treads:

Standard tread width is 350mm by 140mm depth. Alternate sizes between 200mm - 380mm (140mm depth) and 430mm - 580mm (160mm depth) also available.

Fire Rated:

Available 30 minutes or 90 minutes Fire rated. This option has a 1.5mm steel frame and two 1.5mm sheet steel trapdoor. Infilled with 38mm or 75mm mineral wool depending on fire rating requirement.

Loading:

200Kg per tread. 500kg/m² overall structure.

Options:

Electric Operation (See ZIP8E)
Telescopic handrail
Top Guardrail

Fire Rating 30/90 Minute
Top operation - Cable/Pull ring
Cylinder Lock

| STANDARD SIZES | | |
|-------------------------|------------------|-----------------|
| Floor to Ceiling Height | Touch down point | Operating Space |
| 2200 - 2500 | 1350 - 1200 | 1450 |
| 2501 - 2790 | 1450 - 1300 | 1550 |
| 2791 - 3090 | 1550 - 1440 | 1650 |
| 3091 - 3390 | 1660 - 1540 | 1770 |
| 3391 - 3960 | 1770 - 1640 | 1890 |
| 3961 - 3990 | 1880 - 1740 | 2010 |
| 3991 - 4300 | 1980 - 1830 | 2030 |

The floor to ceiling height will determine the length of the structural opening. Contact our sales department for more details.

