

Coxdome Fixed Rooflight

Coxdome Fixed Polycarbonate Flat Roof skylights are manufactured to a high standard with double or triple glazing and a 150mm PVC Upstand. The thermally broken upstand manufactured from PVC plastic profiles ensures a strong thermal performance and resilience to condensation formation.

MATERIAL

- Double or triple polycarbonate layers
- Clear or Opal glazing
- UV Stable PVC-u white Upstand

PERFORMANCE

- U Value 1.7 W/m²K based on triple layer
- 150mm PVC Upstand U-value 1.8 W/m²K
- Class B Non-fragile ACR(M)001:2005
- Sound reduction 22dB

Layer Variant	Number of Layers	Light Transmittance	U-Value
Clear (Double)	2 Layers	77%	2.6 W/m ² K
Diffused (Double)	2 Layers	77%	2.6 W/m ² K
Clear (Triple)	3 Layers	71%	1.7 W/m ² K
Diffused (Triple)	3 Layers	71%	1.7 W/m ² K

Available Sizes

Structural Opening

- 600 x 600
- 600 x 900
- 600 x 1200
- 750 x 750
- 750 x 900
- 800 x 800
- 900 x 900
- 900 x 1200
- 1000 x 1000
- 1000 x 1500
- 1100 x 1100
- 1200 x 1200
- 1200 x 1800

CAD Drawings

