

SRHP

THERMALLY BROKEN ROOF HATCH

SRHP Overview

The Surespan SRHP Aluminium single leaf roof access hatch is thermally broken with 50mm CFC and HCFC free insulation with a U-value of 0.43W/m²K.

The hatch also incorporates safety hold open stay to prevent against accidental closure.

The lid is held shut by an internal stainless steel slam action cablock.

STANDARD FEATURES

- 300mm Upstand insulated
- Thermally Broken Roof Hatch
- Insulated U-value of 0.43W/m²K
- Curb Liner
- External in mill finish aluminium

Material:

Aluminium extrusions in 6063 -T6. Sheet aluminium where used will be 1050 H14.

Cover:

The thermally broken lid incorporates a sandwich of 50mm CFC and HCFC free insulation. The hatch also incorporates a safety hold open stay.

Locking:

The lid is held shut by a heavy duty grade 316 stainless steel Cablock.

Upstand:

Standard height 300mm upstand is filled with 50mm CFC and HCFC free insulation with external curb liner for flashing up against.

Operation:

Complete with gas spring assisted opening to ensure minimum amount of effort to open the double skinned aluminium lid. The lid will have the provision to lock in the open position with a safety hold open stay to prevent against accidental closure.

Finish:

External finished in mill finish aluminium
Internal & External powder coating can be requested to any RAL Colour.

INSULATION OPTIONS	
Model	U-Value
Standard Insulation	0.43 W/m ² K
Premium Insulation	0.37 W/m ² K
Superior Insulation	0.20 W/m ² K

Calculated to BS EN ISO 6946: 2007

STANDARD SIZES (BESPOKE AVAILABLE)	
Model	S/O
SRHP 60.60	600 x 600
SRHP 75.75	750 x 750
SRHP 90.75	900 x 750
SRHP 90.90	900 x 900
SRHP 100.100	1000 x 1000
SRHP 75.150	750 x 1500
SRHP 120.120	1200 x 1200
SRHP 75.250	750 x 2500
SRHP 75.330	750 x 3300

