

SRHP-SS

THERMALLY BROKEN ROOF HATCH

SRHP/TB/SS Overview

The Surespan SRHP/TB Grade 304 or 316 Stainless Steel single leaf roof access hatch is thermally broken with 50mm thick CFC and HCFC free insulation which offers a U-Value of 0.43W/m²K to BS 3958: Part 5:1986. The hatch also incorporates a safety hold open stay to prevent against accidental closure.

The lid is held shut by slam action cablock and external L04 Padlockable Handle.

STANDARD FEATURES

- 300mm Upstand insulated
- Insulated U-value of 0.43W/m²K
- Curb Liner
- Grade 304 or 316 Stainless Steel
- Unique SureClips to secure flashing

Material:	Grade 304 or Grade 316 Stainless Steel.
Cover:	The thermally broken lid incorporates a sandwich of 50mm HCFC and CFC free insulation. The hatch also incorporates a safety hold open stay.
Locking:	The lid is held shut by a heavy duty grade 316 stainless steel Cablock with external padlockable handle.
Upstand:	Standard height 300mm upstand is filled with 50mm insulation and has a purpose made flashing with Sureclips to hold flashing in place.
Operation:	Complete with gas spring assisted opening to ensure minimum amount of effort to open the lid. The lid will have the provision to lock in the open position with a safety hold open stay to prevent against accidental closure.
Finish:	Polished or Satin Stainless Steel Finish

