

SRH/S20
THERMALLY BROKEN SUPERIOR ROOF HATCH
SRH/S20 Overview

The Surespan SRH/S20 Aluminium single leaf roof access hatch is thermally broken with 50mm superior insulation which offers a U-value of 0.20 W/m²K calculated to BS EN ISO 6946:2007.

The hatch also incorporates safety hold open stay to prevent against accidental closure.

The lid is held shut by slam action cablock

STANDARD FEATURES

- 385mm Fully insulated upstand
- Superior insulation offers 0.20 W/m²K**
- Curb Liner included as standard
- External in mill finish aluminium
- Internal Cablock

Material:

Aluminium extrusions in 6063 -T6. Sheet aluminium where used will be 1050 H14.

Cover:

The thermally broken lid incorporates a sandwich of 50mm superior insulation which offers a U-value of 0.20 W/m²K.

Locking:

The lid is held shut by a heavy duty grade 316 stainless steel Cablock. Other locking options are available upon request.

Upstand:

385mm upstand is filled with 50mm superior insulation.

Operation:

Complete with gas spring assisted opening to ensure minimum amount of effort to open the double skinned aluminium lid. The lid will have the provision to lock in the open position with a safety hold open stay to prevent against accidental closure.

Finish:

External finished in mill finish aluminium
Internal & External powder coating can be requested to any RAL Colour.
Also available as stainless steel.

STANDARD SIZES

Model	S/O
SRHP 60.60	600 x 600
SRHP 75.75	750 x 750
SRHP 90.75	900 x 750
SRHP 90.90	900 x 900
SRHP 100.100	1000 x 1000
SRHP 75.150	750 x 1500
SRHP 120.120	1200 x 1200
SRHP 75.250	750 x 2500
SRHP 75.330	750 x 3300

